


Splitters with F connectors 5-2400MHz

SPTR



New CATV **splitters** on frequency range **5-2400MHz** with “**top down**” F connectors.

Compact and good-looking design to fulfill every installation requirement and enable them to be installed in every location.

Zinc die cast housing allows to reach the best performances over all the operating frequency range, with **low insertion loss** up to high frequencies and high isolation between outputs.

DC pass is allowed between every output and input.

Main specifications

- **Low insertion loss** also on SAT band, up to 2400MHz.
- **Changeless attenuation on output ports** from 5 to 2400MHz.
- **DC pass** from outputs to input
- **High return loss**
- “**A**” **shielding factor**
- **2 earth screws**
- **Wall fixing**

SPLITTERS

Code	Item	Insertion Loss					Separation Out-Out				
		40 MHz	862 MHz	950 MHz	2150 MHz	2400 MHz	40 MHz	862 MHz	950 MHz	2150 MHz	2400 MHz
		dB	dB	dB	dB	dB	dB	dB	dB	dB	dB
287305	SPTR2	3,5	4	4	5	5.5	27,5	20	20	18	18
287307	SPTR3	6	7	7	9	9,5	25	20	20	20	18
287306	SPTR4	7	8	8	9,5	10	20	20	20	18	18
287308	SPTR6	10	11	11,5	14,5	16	27,5	25	25	25	25
287309	SPTR8	11	12,5	12,5	15,5	16	27,5	25	25	25	25

Fracarro Code	Item	Product dimensions mm	Packing	EAN Code	Quantity Pc	Packaging dimensions mm	Net Weight kg	Weight kg
287305	SPTR2	55x60x25	Multiple	8016978094820	10	112x127x64	0.82	0.90
287307	SPTR3	55x60x25	Multiple	8016978094844	10	112x127x64	0.82	0.90
287306	SPTR4	77x60x25	Multiple	8016978094875	10	155x127x64	1.03	1.10
287308	SPTR6	100x60x25	Multiple	8016978094899	10	122x254x64	1.43	1.50
287309	SPTR8	120x60x25	Multiple	8016978094912	10	122x254x64	1.43	1.50